



Connection: Positive Lock/RCA/4PIN DIN
Total Pixels Horizontal Resolution: 420 TV Lines
Shock Rating: 10G
Lens View Angle: D: 160° H: 122° V: 93°
Operating Temperature: -20°C ~+70°C
RH95% Max
Storage Temperature: -40°C ~+85°C
RH95% Max
Lens: f=1.7mm(P)/1.7mm (N) F=2.5
White Balance: Auto
S/N Ratio: Better than 48dB
Horizontal Sync Frequency:
15.625KHz/15.734KHz
Vertical Sync Frequency: 50Hz/60Hz
Power Supply: DC 12V
Minimum Illumination: 0 Lux/IR ON
Microphone/Audible Capable: Yes
Video Output: 1.0vp-p, 750hm
Gamma Consumption: 0.45
AGC: Auto
Waterproof Rating: IP68
IR LEDs: 18pcs
Night Vision Distance: 45 Feet
Image Sensor: CMOS
Sensing Area: 3.6mm x 2.7mm
TV System: NTSC/PAL Optional
Effective Pixels: P: 512 x 582 N: 512 x 492
Horizontal Resolution: 420 TV Lines
Sync System: Internal
Heating Chip: Optional
Size: 72(L) x 52(W) x 42(H) mm

Rear View Camera CMOS Imager

- CMOS Imager Technology- great performance at a low cost equals value
- IR LEDs with Night Vision Distance of 45 feet
- Built in microphone with waterproof housing and connector
- Excellent viewing angles of 95 degrees Vertical 120 degrees Horizontal
- Available in Black and White Housing