

# SANSUI Accu D-LED LCD Series – SLED5516 (4K@60Hz)



## BASIC FEATURES

- Ultra High Definition Digital TV (4K2K/60Hz, 4K1K/120Hz Display)
- Integrated Digital Tuner (ATSC, QAM)
- Receives Over-the-Air DTV Broadcast Signals
- 54.6" (16:9) UHD LED (3840 x 2160)
- Brightness 300cd/m<sup>2</sup>
- Contrast ratio 1,000,000:1 (w/DBC)
- Response time 6.5ms
- 3D Comb Filter
- Wall Mount Vesa (TBA)
- Energy Star Ver. 6.1
- Hotel Mode

## JACK CONFIGURATION

- HDMI Input x 4 (HDMI2.0(4K@60Hz) x 1, HDMI1.4 x 2, MHL x 1)
- Component Input x 1
- A/V Input x 1
- PC Monitor Input
- Digital Audio Out (Optical)
- Analog Audio Out (Mini Jack)
- Headphone Jack

## DIMENSIONS

- |                              |                      |
|------------------------------|----------------------|
| • Unit w/stand (W x D x H)   | 49.25"x10.67"x30.63" |
| • Unit w/o stand (W x D x H) | 49.25"x3.46"x28.74"  |
| • Carton (W x D x H)         | 54.25"x6.73"x32.91"  |
| • Unit Weight                | 35.49 lbs            |
| • Carton Weight              | 47.84 lbs            |
| • On Mode Power Consumption  | 140W                 |
| • Unit Color                 | Black                |
| • Container Quantity         | 324/40HQ             |
| • Country of Origin          | China                |
| • UPC#                       | 859087005015         |

## ACCESSORIES

- Remote Control
- Battery 3A x 2

\* All trademark's are the property of their respected owners. Information for reference purposes only. Subject to change without notice. Not responsible for typographical errors.